

The background of the entire image is a dark, almost black, wood texture. The wood grain is visible, with various knots and imperfections. The texture is slightly uneven, with some areas appearing more worn or scratched than others.

GRAN PARADISO BLACK

CHOPPED

GRAN PARADISO BLACK

NORDIC SPRUCE
THERMALLY TREATED AT 212°
BRUSHED, BLACK COATED



DESIGN PANEL

3-LAYER

LENGTH (M): 4,96

DIMENSIONS (mm)		PACKAGING (Pieces)
THICKNESS	WIDTH	PACKAGE SIZE
23	1220 / 2000	20

QUALITY	• Visible Side / Non-Visible Side • Crack- and gap-free • Healthy, firmly attached knots allowed • Filling/repairing knot tears and cracks allowed • Light burls allowed • 10% of the panel may be patched and repaired • Discoloration and fungal infestation not allowed • No knot accumulation
TOP LAYER	Pine Thermo Thickness 8.1 mm
MIDDLE LAYER	Larch Natural Thickness 6.8 mm
BOTTOM LAYER	Pine Thermo Thickness 8.1 mm Non-Visible (Closed)
TOP LAMELLA WIDTH	137 mm
MOISTURE CONTENT	KD 7% ± 2 Ex Works
EMISSION CLASS	E1, Formaldehyde value according to ÖNORM EN 13986 Formaldehyde content ≤ 0.01 ppm
BONDING	Melamine - Urea System Bonding: According to EN 13354 SWP/3 (boil-resistant bonding)
DENSITY	approx. 430 kg/m³, approx. 10 kg/m²
APPLICATION	Interior Use according to CE Certification, Type 4
INFO	The following properties must be observed: • Three-layer solid wood panels are made of solid wood • Swelling and shrinkage behavior must be considered • If the ambient humidity is too high, the wood absorbs moisture, leading to dimensional changes and warping • If the ambient humidity is too dry, slight warping or fine surface cracks may occur • These are natural wood characteristics and not production defects