

The background of the entire image is a close-up, vertical view of a light-colored wood surface. The wood grain is prominent, showing horizontal lines and several dark, circular knots. The lighting is even, highlighting the natural texture of the wood.

MARMOLADA

BRUSHED

MARMOLADA

SPRUCE CHARACTER
STEAMED
BRUSHED



DESIGN PANEL

3-LAYER

LENGTH (M): 3,96

DIMENSIONS (mm)		PACKAGING (Pieces)
THICKNESS	WIDTH	PACKAGE SIZE
20	1220 / 2000	25

QUALITY	<ul style="list-style-type: none">• Visible Side / Non-Visible Side• Crack- and gap-free• Healthy, firmly attached knots allowed• Filling/repairing knot tears and cracks allowed• Light burls allowed• 10% of the panel may be patched and repaired• Discoloration and fungal infestation not allowed• No knot accumulation
TOP LAYER	Spruce Steamed Thickness 5.0 mm
MIDDLE LAYER	Spruce Natural Thickness 10.0 mm
BOTTOM LAYER	Spruce Steamed Thickness 5.0 mm Non-Visible (Closed)
TOP LAMELLA WIDTH	137 mm
MOISTURE CONTENT	KD 8% ± 2 Ex Works
EMISSION CLASS	E1, Formaldehyde value according to ÖNORM EN 13986 Formaldehyde content ≤ 0.01 ppm
BONDING	Melamine - Urea System Bonding: According to EN 13354 SWP/3 (boil-resistant bonding)
DENSITY	approx. 450 kg/m³, approx. 9.0 kg/m²
APPLICATION	Interior Use according to CE Certification, Type 4
INFO	<p>The following properties must be observed:</p> <ul style="list-style-type: none">• Three-layer solid wood panels are made of solid wood• Swelling and shrinkage behavior must be considered• If the ambient humidity is too high, the wood absorbs moisture, leading to dimensional changes and warping• If the ambient humidity is too dry, slight warping or fine surface cracks may occur• These are natural wood characteristics and not production defects