

MARMOLADA VECCHIA

SPRUCE CHARACTER STEAMED CHOPPED EMBOSSED LIGHTLY BRUSHED



DESIGN PANEL

3-LAYER

LENGTH (M): 3,96

DIMENSIONS (mm)		PACKAGING (Pieces)
THICKNESS	WIDTH	PACKAGE SIZE
23	1220 / 2000	20
QUALITY	 Visible Side / Non-Visible Side Crack- and gap-free Healthy, firmly attached knots allowed Filling/repairing knot tears and cracks allowed Light burls allowed 10% of the panel may be patched and repaired Discoloration and fungal infestation not allowed No knot accumulation 	
TOP LAYER	Spruce Steamed Thickness 8.1 mm	
MIDDLE LAYER	Spruce Natural Thickness 6.8 mm	
BOTTOM LAYER	Spruce Steamed Thickness 8.1 mm Non-Visible (Closed)	
TOP LAMELLA WIDTH	137 mm	
MOISTURE CONTENT	KD 8% ± 2 Ex Works	
EMISSION CLASS	E1, Formaldehyde value according to ÖNORM EN 13986 Formaldehyde content ≤ 0.01 ppm	
BONDING	Melamine - Urea System Bonding: According to EN 13354 SWP/3 (boil-resistant bonding)	
DENSITY	approx. 450 kg/m³, approx. 10.3 kg/m²	
APPLICATION	Interior Use according to CE Certification, Type 4	
INFO	 The following properties must be observed: Three-layer solid wood panels are made of solid wood Swelling and shrinkage behavior must be considered If the ambient humidity is too high, the wood absorbs moisture, leading to dimensional changes and warping If the ambient humidity is too dry, slight warping or fine surface cracks may occur These are natural wood characteristics and not production defects 	