

C

A CO

PIZ BUIN

DOMESTIC LARCH Steamed Chopped

DESIGN PANEL

3-LAYERED

LENGTH (M): 3,96

DIMENSIONS (mm)		PACKAGING (Pieces)	
THICKNESS	WIDTH	PACKAGE SIZE	
23	1220 / 2000	20	
QUALITY	 Visible Side / Non-Visible Side Crack- and gap-free Healthy, firmly attached knots allowed Filling/repairing knot tears and cracks allowed Light burls allowed 10% of the panel may be patched and repaired Discoloration and fungal infestation not allowed No knot accumulation 		
TOP LAYER	Larch Steamed Thickness 8.1 mm		
MIDDLE LAYER	Larch Natural Thickness 6.8 mm		
BOTTOM LAYER	Larch Steamed Thickness 8.1 mm Non-Visible (Closed)		
TOP LAMELLA WIDTH	137 mm		
MOISTURE CONTENT	KD 8% ± 2 Ex Works		
EMISSION CLASS	E1, Formaldehyde value according to ÖNORM EN 13986 Formaldehyde content ≤ 0.01 ppm		
BONDING	Melamine - Urea System Bonding: According to EN 13354 SWP/3 (boil-resistant bonding)		
DENSITY	approx. 600 kg/m³, approx. 13.8 kg/m²		
APPLICATION	Interior Use according to CE Certification, Type 4		
INFO	 Three-layer solid wood panels a Swelling and shrinkage behavior If the ambient humidity is too hi dimensional changes and warpii If the ambient humidity is too do occur 	he ambient humidity is too dry, slight warping or fine surface cracks may	