

The background of the entire image is a close-up, high-resolution photograph of dark grey, weathered wood. The wood grain is prominent, showing horizontal lines and several knots. The texture is rough and aged, with varying shades of grey and brown.

**ZERMATT**  
GRIS

# ZERMATT GRIS

ORIGINAL RECLAIMED WOOD  
SPRUCE / FIR / PINE  
SUNBURNT GREY



## ALPINE WALL PANELS

PROFILE BOARD READY FOR PLACEMENT

LENGTHS (M): 1,0 - 3,0 (random lengths)

DIMENSIONS (mm)			PACKAGING
THICKNESS	WIDTH		
	Tongue Measurement	Covering Dimension	
18	107-217mm in whole centimetre increments	+8mm to the respective tongue measurement	bundled to 5 layers each; fair length distribution in the bundle

WOOD TYPE	Spruce / Fir / Pine
PROFILING	four-sided
STANDARD	CE EN 14915
MOISTURE CONTENT	kd 8% +/- 2
DENSITY	ca. 12 kg/m <sup>2</sup>
SURFACE TREATMENT	brushed
APPLICATION	Indoor and outdoor use
MODIFICATION	original sunburnt, grey

ADVANTAGE:  
Four-sided profiling enables quick installation with minimal waste.

## SOLID BOARDS

ORIGINAL SUNBURNT BOARDS, DE-NAILED WITH DETECTOR, TRIMMED,  
REVERSE SIDE PLANED.

LENGTHS (M): 1,5 - 4,0 (4+ upon request)

DIMENSIONS (mm)		
THICKNESS	WIDTH	PACKAGING
20	100-250mm	Sorted in meter increments, slatted, and bundled in packages.

WOOD TYPE	Spruce / Fir / Pine
MOISTURE CONTENT	kd 12% +/- 2
DENSITY	ca. 500 kg/m <sup>3</sup>
MODIFICATION	original sunburnt, grey